BEST AVAILABLE COPY

04-13-'06 16:16 FROM-LGS PatentUSA

• 1

+9549251101

T-617 P02/06 U-610

Application No.: 10/237,542 Amdt. dated 4/13/05

Reply to Office action dated 3/15/06

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claim 1 (currently amended). A method for controlling a quantity of medium transferable from a screen roller of a printing machine onto a roller that is in contact

with the screen roller, which comprises:

exerting an influence upon a difference in circumferential speed between the screen

roller and the roller in contact therewith, and [further comprises] controlling the

difference in the circumferential speed as a function of the printing speed of the

printing machine, so that printed medium density remains at least approximately

constant at least within a wide printing speed range; and

determining, for the difference in the circumferential speed dependent upon the

printing speed, a characteristic curve at which the printed medium density remains

constant, and storing the characteristic curve in a control device.

Claim 2 (currently amended). The method according to claim 1, wherein the medium

controlled thereby is a medium selected from the group [thereof] consisting of ink

and varnish.

Page 2 of 5

+9549251101

T-617 P03/06 U-610

Application No.: 10/237,542

Amdt. dated 4/13/05

Reply to Office action dated 3/15/06

Claim 3 (original). The method according to claim 1, wherein the difference in

circumferential speed is zero at a standard printing speed.

Claim 4 (original). The method according to claim 1, wherein the difference in circumferential speed is zero at a printing speed higher than a standard printing speed.

Claim 5 (canceled).

Claim 6 (canceled).

Claim 7 (original). The method according to claim 1, which further comprises controlling the difference in the circumferential speed as a function of a circumferential speed of a cylinder selected from the group thereof consisting of a printing-form cylinder and a blanket cylinder capable of being supplied with the medium by the screen roller.

Claim 8 (original). The method according to claim 1, which further comprises increasing the temperature of the screen roller so as to raise the printed medium density.

Claim 9 (original). The method according to claim 1, which further comprises lowering the temperature of the screen roller so as to reduce the printed medium density.

Page 3 of 5